\$11) 3000

- designed to exceed everyday demands in all applications
- stringent engineering and testing practices
- highest efficiency and durability in the harshest conditions










SHD 3000 LED

The SHD 3000 LED series work lights are designed to exceed everyday demands in all applications. Through stringent engineering and testing practices, we ensure the highest efficiency and durability in even the harshest operating conditions.

Dimensions



20 12 7 3,5


Light Patterns

40

30

20

40 30 20 10





0 10 20 30 40

50

30 20

Specifications


Bulb	6 LED - 3000 Lumen
Lifetime	20 000 hours
Color temperature	6000K
Light pattern	Flood Asymmetric, Wide Flood, Flood, Long Range
Consumption	36W
Voltage	Multi 12-100V
Intensity	1,5 Amp @ 24V
Weight	0,9 Kg
Vibration resistance	15 Grms from 24 to 2000Hz
Shock resistance	60 G
EMC	ISO 13 766 - ISO 14 982 - ISO 12 895 - CISPR25
Load Dump	130V continuous 200V 100 ms 1800V 50 µs
Polarity	protected against reverse voltage
Electronic Thermal Management	full output @ +35°C ambient 20% dimmed @ +50°C ambient
Water Tightness	IP 68 - IP 69K
Operating Temp	-40°C to +85°C
Salt Spray	ISO 9227
Lens	hardened glass
Reflector	multi lens system
Warranty	20 000 operating hours or 4 years

Connection




Built-in AMP 2 ways E

Options



Mounting



www.abllights.com