512000

- designed to exceed everyday demands in all applications
- stringent engineering and testing practices
- highest efficiency and durability in the harshest conditions











ST 2000 | | | | | | | |

The ST 2000 LED series are compact LED work lights, designed for highest efficiency and durability, in even the harshest operating conditions, thanks to stringent engineering and long term partnership with major Original Equipment Manufacturers.

Dimensions








Dimension unit in mm (10th inch)

3,5

Light Patterns









Specifications

Bulb	10 LED - 2000 Lumen
Lifetime	20 000 hours
Color temperature	6000K
Light pattern Hardened glass lens	Flood Asymmetrical, Flood, Long Range
Light pattern Plastic cover Lens	Flood Asymmetrical, Flood
Light pattern Plastic Lens	Flood
Consumption	22W
Voltage	Multi 12-24V
Intensity	0,92 Amp @ 24V
Weight	0,7 Kg
Vibration resistance	15 Grms from 24 to 2000Hz
Shock resistance	60 G
EMC	ISO 13766, ISO 14982, ISO 12895, CISPR25
Load Dump	36V continuous 58V 160 ms 1800V 50 µs
Polarity	no polarity
Electronic Thermal Management	full output @ +35°C ambiant 20% dimmed @ +50°C ambiant
Water Tightness	IP 68 - IP 69K
Operating Temp	-40°C to +85°C
Salt Spray	ISO 9227
Lens	Hardened glass, plastic cover lens, plastic lens
Reflector	free form reflector
Warranty	20 000 operating hours or 5 years

Connection





Built-in AMP 2 ways

DT 2 ways

Options







Amber blastic



Red Plastic



Rlue Plastic





Magnetic base

Mounting





Suspended

www.abllights.com