



W = Width, D = Depth, H = Height

230V~ 50Hz



PlugIn relay (12V)

DEFA PlugIn Relay 854 is embedded in a suitable polyamide material. The relay contains solid brass rail connectors to ensure long time durability.

DEFA AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

Item number

460854 (Weight: 59gr.)

EAN code: 7042284608544

Assembly box: 100 ex.

Part of

DEFA PlugIn Relay 854 is available in DEFA WarmUp including the battery charger, MultiCharger 1204, and as a single unit.

Use & Installation

DEFA PlugIn Relay 854 can be used together with both the SmartStart™ and Futura timer.

The relay is only to be connected to positive (X) red cable from a DEFA timer. The relay get its negative signal through the PlugIn extension cable connected to the PlugIn connector (Y).

Refer to enclosed product user and installation guide.

Technical specifications

Voltage: [V/Hz]	230 +/- 5%
Operating temperature [°C]	-40/+80
W/H/D [mm]	56/63/70
Weight [gram]	59
IP rating [IP]	44
Insulation class [cl]	II
Certification - Safety	EN 50066:1992 EN 61058-1:2002; A2
Certification - EMC	EN 61058-1:2002; A2 EN 61000-3-2:2006 EN 61000-3-3:1995; A1; A2

www.defa.com