

ATLAS LED - Ref. 212120



The ATLAS LED beacon meets the high requirements of the manufacturer's specifications.

Special attention has been paid to the thermal management of LEDs to ensure optimum service life and operation in the most extreme situations.

TECHNICAL CHARACTERISTICS

Brand	VIGNAL
Product Type	Complete lamp
Voltage	9/32V
Source	LED
Consumption	11W
Color	Amber / Orange
Connector	Naked cable extremity
Fixation	3 vis on Ø 130mm (DIN 14620)
Lens Material	Polycarbonate
Diameter	140 mm
Height	82 mm
Weight	0,45 Kg
Flash Patterns	Rotative
IP protection	IP69K
Polarity	Protected against reverse voltage
Operation Temperatures	-40°C to +80°C

www.vignal-group.com - contact@vignal-group.com

France Lyon HQ : +33 (0)4 72 917 917
 France Caen : +33 (0)2 31 74 73 13
 France Le Mans : +33 (0)2 43 50 14 14

Switzerland Rancate : +41 (0) 91 640 50 80
 US Mosinee : +1 715 693 1530
 China Changzhou : +86 137 7686 3469



Print date : 03/01/2026

ATLAS LED - Ref. 212120

EMC	CISPR25 Class 5, ECE R10
ECE	ECE R65
SAE	SAE Class 2
Industry	Agriculture, Construction, Forestry, Handling and Forklifts, Priority vehicle, Trailers and Semi-trailers, Trucks, Vans and Chassis cab

OTHER VISUALS

